

## IT1813 Instrument Tray with Solid Plain Base

Long Life Re-usable Polypropylene Instrument Tray for use in Sterile Services, Decontamination Units, Hospitals and Clinics



The Warwick Range of polypropylene products from Warwick SASCo was originally designed to offer an alternative to stainless steel products traditionally used in Hospitals.

This Range is now widely used in Sterile Services and Decontamination Units, Operating Rooms and Clinics due to its low cost, effective product design, and repeat performance results in hospital autoclaves.

Easily recognised by its distinct blue colour, the Warwick Range includes bowls, gallipots, kidney dishes, instrument trays, instrument protection, instrument boxes, traceability tags, measuring jugs, scope and instrument



### Product Benefits

- Lightweight, strong and durable - 50% lighter than stainless steel.
- Improved removal of blood residue compared to stainless steel.
- Grip feature moulded below the rim to improve holding.
- Smooth edges and surfaces eliminate paper rips during packing and sterilization.
- Can be sterilized by Autoclave, Ethylene Oxide or Hydrogen Plasma.
- Lid available to order separately.

### Product Specification

- Instrument Tray with Solid Plain Base
- 181mm x 134mm x 54mm
- Pack Size 38
- Registered as a Class 1 Medical Device (CE Marked)
- Complies with following Standards:
  - **ISO 9001:2008**  
Quality Management System
  - **ISO 13485:2003**  
Medical Devices - Quality Management System
  - **ISO 17664:2004**  
Sterilization of Medical Devices - Guidelines for the processing of re-sterilizable medical devices
- Manufactured from high quality polypropylene
- Autoclavable up to 135 ° C

### Guide to Using Warwick Products from Warwick SASCo

#### Cleaning

- Product should be washed before first use.
- Warwick Products are designed for a lengthy service and guaranteed for 1000 washes and sterilizations. Scouring and abrasive cleaners will reduce the performance of products.
- Product should be processed complying with requirements of ISO 17664.

#### Storage

- This product has a shelf life of 12 months from date of manufacture providing the recommended storage conditions are adhered to.
- Product should be stored in its primary packaging, off the floor on a pallet or shelf, and in a clean dry ventilated room at a temperature of 4 °C - 25 °C.